



Maintenance Data – RESILIENT ATHLETIC FLOORING 09 65 66

EcoFitness Maintenance Instructions

Solid Color and Flecksibles Interlocking Tile and Sheet Flooring ...
Plus, Naturals UV Coated Interlocking Tile

Steps	Cleaning Products	Dilute oz. / gal*	Approx Coverage sq. ft. / gal*	Equipment
Initial / Regular Maintenance	Taski profi™	2 – 3 oz.	200 – 400	Sponge mop followed with a wet vacuum or commercial electric scrubber/extractor.
Spot Cleaning	Wet area with Taski profi™	1 oz.	200 – 400	Sponge mop, damp cloth or paper towel
Heavy Soil	Taski Profi	32 oz.	200 – 400	Sponge mop followed with a wet vacuum or commercial electric scrubbing/extractor.

Maintenance Procedures -- Initial and Regular Maintenance

1. Remove all surface dirt and debris by vacuuming, sweeping, damp cloth or sponge mopping. Commercial grade electric floor scrubber/extractor equipment is recommended for large or high traffic areas. If using a commercial floor cleaner, use the softest bristle attachment available with a minimum amount of pressure.
2. Scrub area with a cleaning product which has
 - a) A neutral pH (7-9)
 - b) Low solids
 - c) Low VOC's such as Taski Profi™ cleaner mixed to the manufacturers instructions.
3. Remove soiled solution with a wet vacuum or floor extractor.
4. Rinse with clean water and remove with a wet vacuum or floor extractor.
5. Repeat rinsing until water removed is clean.
6. Allow to dry before use.